



BSM SEAL

Recessed ceiling-mounted downlights with symmetrical light distribution to achieve task, accent or general lighting.

Circular design with trimless appearance. Available in 2 diameters: 120mm and 151mm.

Protection rating against dust and moisture: IP65 from underneath.

Aluminium trim and interior circle powder painted in various finishes, customized RAL under request.

To complete the effect of this fixture, it is also recommended that the inner ring should be painted the same RAL colour as the ceiling.

High purity anodised aluminium reflector in various finishes: specular or sandblasted depending on the beam angle outcome.

Interior trim of die-cast aluminium and tempered flush glass sealed with a silicone gasket.

Tridonic remote driver included.

Passive temperature management: heat dissipation flows through an aluminium heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Suggested applications: kitchens, bathrooms, spas, porches, balconies and similar high humidity environments. Designed to create an exclusive and clean flush installation.

CRI >90	2700K	3000K	4000K	SDCM 3	IP65	A+ A++
---------	-------	-------	-------	--------	------	--------



∅ 120mm

± 116mm
± 126mm

24° 36°



480lm - 1270lm


5W - 12.2W



∅ 151mm

± 138mm
± 148mm

21° 33°



480lm - 1270lm

5W - 12.2W



∅ 151mm

± 122mm
± 132mm

24° 36°



480lm - 1270lm

5W - 12.2W

ELECTRONIC OPTIONS

On/Off.


Phase Cut.

0-10V / 1-10V.

DALI/DSI/switchDIM/corridorFUNCTION.

Emergency Kit.

SPECIAL APPLICATIONS



ACCESSORIES AND FINISHES

