



# SUPER

Surface mounted downlights with symmetrical light distribution.

Cylindrical design available in 2 diameters 180mm and 235mm.

Protection rating against dust and moisture: entire IP65.

Protection rating for resistance to harmful mechanical impacts: IK07.

High-purity aluminium reflectors in various finishes depending on the beam angle outcome. Top reflector: faceted metalized or sandblasted anodised depending on the beam angle outcome. Bottom reflector: sandblasted.

Robust body and trim made of die-cast aluminium treated against corrosion and coated with polyester powder painting available in various colour finishes, customized RAL under request.

5mm tempered protection glass clear as standard.

Temperature resistant silicone rubber gasket.

Anti-condensation device.

Built-in Tridonic driver.

Passive temperature management: heat dissipation through the fixture body itself.

Mounting to the ceiling by two securing points in a bracket. Cable entry from the top of the fixture.

**Suggested applications:** porches, shopping centres, leisure areas, car parks, service stations, industrial facilities, outdoor ceilings in high humidity areas, or interior spaces that require low-maintenance. Solid ceilings or where there is not space for recessed mounting.

IP65 SURFACE MOUNTED DOWNLIGHTS

CRI >80	2700K	3000K	4000K	SDCM 3	IP65	IK07	A <sup>++</sup>
---------	-------	-------	-------	--------	------	------	-----------------



ø 180mm			
± 250mm			
26°	39°	77°	112°
1900lm - 3850lm			
12W - 24W			



ø 235mm				
± 280mm				
13°/16°	24°/27°	36°/38°	96°/97°	109°
1900lm - 5770lm				
12W - 36W				

## ELECTRONIC OPTIONS

On/Off.  
DALI/DSI/switchDIM/corridorFUNCTION.  
Emergency Kit.

## ACCESSORIES AND FINISHES

+ IK 10	+ ELEC	+ INSTAL	RAL

