

Beam

Beam takes the classic downlight to another level of direct lighting with a great light and wide range.

Orientable and adjustable, Beam can respond to every need for general and detail lighting. Now available with a square frame, XL size and asymmetrical versions.



Beam

Body

Aluminium body and heat sink. Aluminium trim attached by traction, with electrostatic 100% polyester paint finish. Available in fixed and adjustable versions (oriented by 30° horizontal rotation and 355° vertical rotation).

Light source

COB LED light source with excellent colour consistency (3 step-MacAdam) and long lifespan (>50.000h; L80/B10).

Accessories


Trimless version with recessing accessories supplied separately.

Diffuser

Diffused beam version supplied with prismatic acrylic diffuser (IP54). Acrylic diffuser for non-diffuse beam versions supplied separately (available only for fixed versions). This accessory allows an increase of the protection level up to IP54 (on the visible body).



Beam



.01 White



.01 White



.02 Black



.02 Black




.32 White + Black




.31 Black + White


Beam Q




.01 White



.02 Black





.32 White + Black




.31 Black + White

Adjustable


The beam of the luminaire can be oriented by 30° horizontal rotation and 355° vertical rotation.




Spot




Medium




Flood



Wide flood



Diffuse



Asymmetric

Beam


Beam

Beam Asymmetric

XL Fixed	Trim Ø200mm / Trimless Ø190mm			
L Fixed Adjustable	Trim Ø150mm / Trimless Ø140mm			
M Fixed Adjustable	Trim Ø110mm / Trimless Ø100mm		Trim Ø110mm	
S Fixed Adjustable	Trim Ø90mm / Trimless Ø75mm			
Accessory		Accessory IP54 Clear diffuser (for fixed versions)		




Adjustable

The beam of the luminaire can be oriented by 30° horizontal rotation and 355° vertical rotation.



Beam Q

Beam Q Asymmetric

	2700K	3000K	4000K
Trim Ø200mm	33W / 3000lm	33W / 3800lm	33W / 3950lm
			
Trim Ø150mm	17W / 1500lm	17W / 1900lm	17W / 2000lm
	24W / 2000lm	24W / 2500lm	24W / 2650lm
Trim Ø110mm	9W / 850lm	9W / 1050lm	9W / 1150lm
			
Trim Ø110mm			
			
Trim Ø90mm	6W / 600lm	6W / 700lm	6W / 750lm
			
	Accessory IP54 Clear diffuser (for fixed versions)		

Finishes

○ .01 White

● .02 Black

◐ .31 Black + White

◑ .32 White + Black

Beam S



Ceiling-recessed luminaire made of aluminium.
Available in fixed and adjustable versions (oriented by 30° horizontal rotation and 355° vertical rotation).
IP54 prismatic acrylic diffuser for the diffused beam version included.

IP54 acrylic diffuser for non-diffuse beam versions supplied separately (available only for fixed versions).
Recessing system with spring clips.

LED CRI>80, 2700K CRI>90 / >50.000h, L80/B10
3-step MacAdam / power supply included



IP20/ IP54 versions with diffuser | 230Vac | 50/60Hz




Optional

IP54 Clear diffuser
(for fixed versions: medium and flood)
28782



Beam S



Medium 28°




Flood 41°



Diffuse



	Light Source Power	Light Source Flux	Luminaire Flux	On/Off Code	DALI Code
Beam S					
Fixed					
					
LED					
2700K					
Medium	6W	600lm	325lm	28036	28785
Flood	6W	600lm	500lm	28037	28786
Diffuse	6W	600lm	300lm	28629	28977
3000K					
Medium	6W	700lm	380lm	28039	28787
Flood	6W	700lm	550lm	28040	28788
Diffuse	6W	700lm	350lm	28630	28978
4000K					
Medium	6W	750lm	410lm	28042	28789
Flood	6W	750lm	600lm	28043	28790
Diffuse	6W	750lm	400lm	28631	28979

Beam S

Adjustable



LED

2700K

Medium	6W	600lm	325lm	28198	28917
Flood	6W	600lm	500lm	28199	28918

3000K

Medium	6W	700lm	380lm	28201	28919
Flood	6W	700lm	550lm	28202	28920

4000K

Medium	6W	750lm	410lm	28204	28921
Flood	6W	750lm	600lm	28205	28922

Finishes

○ .01 White

● .02 Black

● .29 Gold + White

● .30 Gold + Black

● .31 Black + White

● .32 White + Black

Beam S



Optional

IP54 Clear diffuser
(for fixed versions: medium and flood)

28782



Not included

Recessing accessory

28776



Ceiling-recessed luminaire made of aluminium.
Available in fixed and adjustable versions (oriented by 30° horizontal rotation and 355° vertical rotation).
IP54 prismatic acrylic diffuser for the diffused beam version included.

IP54 acrylic diffuser for non-diffuse beam versions supplied separately (available only for fixed versions).
Recessing accessories supplied separately.


LED CRI>80, 2700K CRI>90 / >50.000h, L80/B10
3-step MacAdam / power supply included



IP20/ IP54 versions with diffuser | 230Vac | 50/60Hz



Beam S Trimless



Medium 28°




Flood 41°



Diffuse



	Light Source Power	Light Source Flux	Luminaire Flux	On/Off Code	DALI Code
Beam S Trimless					
Fixed					
					
LED					
2700K					
Medium	6W	600lm	325lm	28045	28791
Flood	6W	600lm	500lm	28046	28792
Diffuse	6W	600lm	300lm	28632	28980
3000K					
Medium	6W	700lm	380lm	28048	28793
Flood	6W	700lm	550lm	28049	28794
Diffuse	6W	700lm	350lm	28633	28981
4000K					
Medium	6W	750lm	410lm	28051	28795
Flood	6W	750lm	600lm	28052	28796
Diffuse	6W	750lm	400lm	28634	28982

Beam S Trimless

Adjustable



LED

2700K

Medium	6W	600lm	325lm	28207	28923
Flood	6W	600lm	500lm	28208	28924

3000K

Medium	6W	700lm	380lm	28210	28925
Flood	6W	700lm	550lm	28211	28926

4000K

Medium	6W	750lm	410lm	28213	28927
Flood	6W	750lm	600lm	28214	28928

Finishes ○ .01 White ● .02 Black ● .35 Gold

Beam M



Ceiling-recessed luminaire made of aluminium.
Available in fixed and adjustable versions (oriented by 30° horizontal rotation and 355° vertical rotation).
IP54 prismatic acrylic diffuser for the diffused beam version included.

IP54 acrylic diffuser for non-diffuse beam versions supplied separately (available only for fixed versions).
Recessing system with spring clips.

LED CRI>80, 2700K CRI>90 / >50.000h, L80/B10
3-step MacAdam / power supply included



IP20/ IP54 versions with diffuser | 230Vac | 50/60Hz




Optional

IP54 Clear diffuser
(for fixed versions: medium and flood)
28783



Beam M



Medium 20°




Flood 40°



Diffuse



	Light Source Power	Light Source Flux	Luminaire Flux	On/Off Code	DALI Code
Beam M					
Fixed					
					
LED					
2700K					
Medium	9W	850lm	650lm	28054	28797
Flood	9W	850lm	700lm	28055	28798
Diffuse	9W	850lm	450lm	28665	28983
3000K					
Medium	9W	1050lm	800lm	28057	28799
Flood	9W	1050lm	850lm	28058	28872
Diffuse	9W	1050lm	550lm	28666	28984
4000K					
Medium	9W	1150lm	850lm	28060	28873
Flood	9W	1150lm	900lm	28061	28874
Diffuse	9W	1150lm	600lm	28667	28985

Beam M

Adjustable



LED

2700K

Medium	9W	850lm	650lm	28306	28929
Flood	9W	850lm	700lm	28307	28930

3000K

Medium	9W	1050lm	800lm	28309	28931
Flood	9W	1050lm	850lm	28310	28932

4000K

Medium	9W	1150lm	850lm	28312	28933
Flood	9W	1150lm	900lm	28313	28934


Finishes

 .01 White

 .02 Black

 .29 Gold + White

 .30 Gold + Black

 .31 Black + White

 .32 White + Black

Beam M



Optional

IP54 Clear diffuser
(for fixed versions: medium and flood)

28783



Not included

Recessing accessory

28777



Ceiling-recessed luminaire made of aluminium.
Available in fixed and adjustable versions (oriented by 30° horizontal rotation and 355° vertical rotation).
IP54 prismatic acrylic diffuser for the diffused beam version included.

IP54 acrylic diffuser for non-diffuse beam versions supplied separately (available only for fixed versions).
Recessing accessories supplied separately.


LED CRI>80, 2700K CRI>90 / >50.000h, L80/B10
3-step MacAdam / power supply included



IP20/ IP54 versions with diffuser | 230Vac | 50/60Hz



Beam M Trimless




Medium 20°




Flood 40°



Diffuse



	Light Source Power	Light Source Flux	Luminaire Flux	On/Off Code	DALI Code
Beam M Trimless					
Fixed					
					
LED					
2700K					
Medium	9W	850lm	650lm	28063	28875
Flood	9W	850lm	700lm	28064	28876
Diffuse	9W	850lm	450lm	28668	28986
3000K					
Medium	9W	1050lm	800lm	28066	28877
Flood	9W	1050lm	850lm	28067	28878
Diffuse	9W	1050lm	550lm	28669	28987
4000K					
Medium	9W	1150lm	850lm	28069	28879
Flood	9W	1150lm	900lm	28070	28880
Diffuse	9W	1150lm	600lm	28670	28988

Beam M Trimless

Adjustable

					
LED					
2700K					
Medium	9W	850lm	650lm	28315	28935
Flood	9W	850lm	700lm	28316	28936
3000K					
Medium	9W	1050lm	800lm	28318	28937
Flood	9W	1050lm	850lm	28319	28938
4000K					
Medium	9W	1150lm	850lm	28321	28939
Flood	9W	1150lm	900lm	28322	28940

Finishes ○ .01 White ● .02 Black ● .35 Gold

Beam L



Optional


IP54 Clear diffuser

(for fixed versions: spot, flood and wide flood)

28784



Beam L



Spot 15°



Flood 36°



Wide flood 51°



Diffuse



Ceiling-recessed luminaire made of aluminium.

Fixed version.

IP54 prismatic acrylic diffuser for the diffused beam version included.

IP54 acrylic diffuser for non-diffuse beam versions supplied separately.

Recessing system with spring clips.


LED CRI>80, 2700K CRI>90 / >50.000h, L80/B10

3-step MacAdam / power supply included



IP20/ IP54 versions with diffuser | 230Vac | 50/60Hz



	Light Source Power	Light Source Flux	Luminaire Flux	On/Off Code	DALI Code
Beam L					
Fixed					
					
LED					
2700K					
Spot	17W	1500lm	1150lm	28089	28899
	24W	2000lm	1500lm	28071	28881
Flood	17W	1500lm	1150lm	28090	28900
	24W	2000lm	1500lm	28072	28882
Wide flood	17W	1500lm	1150lm	28091	28901
	24W	2000lm	1500lm	28073	28883
Diffuse	17W	1500lm	750lm	28737	28995
	24W	2000lm	1000lm	28701	28989
3000K					
Spot	17W	1900lm	1450lm	28092	28902
	24W	2500lm	1900lm	28074	28884
Flood	17W	1900lm	1450lm	28093	28903
	24W	2500lm	1900lm	28075	28885
Wide flood	17W	1900lm	1450lm	28094	28904
	24W	2500lm	1900lm	28076	28886
Diffuse	17W	1900lm	950lm	28738	28996
	24W	2500lm	1250lm	28702	28990
4000K					
Spot	17W	2000lm	1500lm	28095	28905
	24W	2650lm	2000lm	28077	28887
Flood	17W	2000lm	1500lm	28096	28906
	24W	2650lm	2000lm	28078	28888
Wide flood	17W	2000lm	1500lm	28097	28907
	24W	2650lm	2000lm	28079	28889
Diffuse	17W	2000lm	1000lm	28739	28997
	24W	2650lm	1350lm	28703	28991

Finishes ○ .01 White ● .02 Black ● .29 Gold + White ● .30 Gold + Black ● .31 Black + White ● .32 White + Black

Beam L



Ceiling-recessed luminaire made of aluminium.
Adjustable version (oriented by 30° horizontal rotation and 355° vertical rotation).
Recessing system with spring clips.


LED CRI>80, 2700K CRI>90 / >50.000h, L80/B10
3-step MacAdam / power supply included



IP20 | 230Vac | 50/60Hz



Beam L



Spot 15°




Flood 36°



Wide flood 51°



	Light Source Power	Light Source Flux	Luminaire Flux	On/Off Code	DALI Code
Beam L					
Adjustable					
					
LED					
2700K					
Spot	17W	1500lm	1150lm	28521	28959
	24W	2000lm	1500lm	28413	28941
Flood	17W	1500lm	1150lm	28522	28960
	24W	2000lm	1500lm	28414	28942
Wide flood	17W	1500lm	1150lm	28523	28961
	24W	2000lm	1500lm	28415	28943
3000K					
Spot	17W	1900lm	1450lm	28524	28962
	24W	2500lm	1900lm	28416	28944
Flood	17W	1900lm	1450lm	28525	28963
	24W	2500lm	1900lm	28417	28945
Wide flood	17W	1900lm	1450lm	28526	28964
	24W	2500lm	1900lm	28418	28946
4000K					
Spot	17W	2000lm	1500lm	28527	28965
	24W	2650lm	2000lm	28419	28947
Flood	17W	2000lm	1500lm	28528	28966
	24W	2650lm	2000lm	28420	28948
Wide flood	17W	2000lm	1500lm	28529	28967
	24W	2650lm	2000lm	28421	28949

Finishes ○ .01 White ● .02 Black ● .29 Gold + White ● .30 Gold + Black ● .31 Black + White ● .32 White + Black

Beam L



Optional

IP54 Clear diffuser

(for fixed versions: spot, flood and wide flood)

28784




Not included

Recessing accessory

28778



Beam L Trimless



Spot 15°



Flood 36°



Wide flood 51°



Diffuse



Ceiling-recessed luminaire made of aluminium.

Fixed version.

IP54 prismatic acrylic diffuser for the diffused beam version included.

IP54 acrylic diffuser for non-diffuse beam versions supplied separately.

Recessing accessories supplied separately.


LED CRI>80, 2700K CRI>90 / >50.000h, L80/B10

3-step MacAdam / power supply included



IP20/ IP54 versions with diffuser | 230Vac | 50/60Hz



	Light Source Power	Light Source Flux	Luminaire Flux	On/Off Code	DALI Code
Beam L Trimless					
Fixed					
					
LED					
2700K					
Spot	17W	1500lm	1150lm	28098	28908
	24W	2000lm	1500lm	28080	28890
Flood	17W	1500lm	1150lm	28099	28909
	24W	2000lm	1500lm	28081	28891
Wide flood	17W	1500lm	1150lm	28100	28910
	24W	2000lm	1500lm	28082	28892
Diffuse	17W	1500lm	750lm	28740	28998
	24W	2000lm	1000lm	28704	28992
3000K					
Spot	17W	1900lm	1450lm	28101	28911
	24W	2500lm	1900lm	28083	28893
Flood	17W	1900lm	1450lm	28102	28912
	24W	2500lm	1900lm	28084	28894
Wide flood	17W	1900lm	1450lm	28103	28913
	24W	2500lm	1900lm	28085	28895
Diffuse	17W	1900lm	950lm	28741	28999
	24W	2500lm	1250lm	28705	28993
4000K					
Spot	17W	2000lm	1500lm	28104	28914
	24W	2650lm	2000lm	28086	28896
Flood	17W	2000lm	1500lm	28105	28915
	24W	2650lm	2000lm	28087	28897
Wide flood	17W	2000lm	1500lm	28106	28916
	24W	2650lm	2000lm	28088	28898
Diffuse	17W	2000lm	1000lm	28742	29500
	24W	2650lm	1350lm	28706	28994

Finishes ○ .01 White ● .02 Black ● .35 Gold

Beam L



Ceiling-recessed luminaire made of aluminium.
Adjustable version (oriented by 30° horizontal rotation and 355° vertical rotation).
Recessing accessories supplied separately.


LED CRI>80, 2700K CRI>90 / >50.000h, L80/B10
3-step MacAdam / power supply included




IP20 | 230Vac | 50/60Hz



Not included
Recessing accessory
28778



Beam L Trimless



Spot 15°




Flood 36°



Wide flood 51°



	Light Source Power	Light Source Flux	Luminaire Flux	On/Off Code	DALI Code
Beam L Trimless					
Adjustable					
					
LED					
2700K					
Spot	17W	1500lm	1150lm	28530	28968
	24W	2000lm	1500lm	28422	28950
Flood	17W	1500lm	1150lm	28531	28969
	24W	2000lm	1500lm	28423	28951
Wide flood	17W	1500lm	1150lm	28532	28970
	24W	2000lm	1500lm	28424	28952
3000K					
Spot	17W	1900lm	1450lm	28533	28971
	24W	2500lm	1900lm	28425	28953
Flood	17W	1900lm	1450lm	28534	28972
	24W	2500lm	1900lm	28426	28954
Wide flood	17W	1900lm	1450lm	28535	28973
	24W	2500lm	1900lm	28427	28955
4000K					
Spot	17W	2000lm	1500lm	28536	28974
	24W	2650lm	2000lm	28428	28956
Flood	17W	2000lm	1500lm	28537	28975
	24W	2650lm	2000lm	28429	28957
Wide flood	17W	2000lm	1500lm	28538	28976
	24W	2650lm	2000lm	28430	28958

Finishes ○ .01 White ● .02 Black ● .35 Gold