



GANIMEDE

Incasso **IP67** con vetro quadrato, per installazione a filo pavimento/parete, ideale per l'illuminazione di marciapiedi, vialetti, giardini, pavimentazioni in porfido.

*Recessed **IP67** fixture, with square glass, for flush floor and wall applications, ideal for the lighting of sidewalks, paths, gardens, porphyry cobbles.*




GANIMEDE S



GANIMEDE L

GANIMEDE L

GANIMEDE




Materiale <i>Material</i>	Corpo in alluminio anticorodal anodizzato <i>Anticorodal anodized aluminium body</i>		
	Vetro temperato sabbaiato <i>Sandblasted tempered glass</i>		
Pot. Assorbita <i>Abs. Power</i>	<i>S version</i> <i>L vesion</i>	1 x 2W 1 x 6W	
Collegamento <i>Connection</i>	24Vdc - Parallelo <i>Parallel</i>		
Cablaggio <i>Wiring</i>	Fornito con 50 cm di cavo e WP System <i>Provided with 50 cm cable and WP System</i>		
Installazione <i>Installation</i>	A incasso a terra con cassaforma (non inclusa) <i>Recessed on ground with housing box (not included)</i>		
	Drenaggio 30 cm di ghiaia <i>30 cm gravel drainage</i>		
	Calpestabile <i>Walk-over</i>		
Alimentatore <i>Power supply</i>	2 - 6W - 24Vdc (Non incluso <i>Not included)</i>		
Finitura <i>Finishing</i>	 .13 Vetro <i>Glass</i>		

- 2700 K**
- 5000 K** (Solo versione S | *S version only*)
- RGBW** (Solo versione L in C.C., senza WP System)
RGBW (L in C.C. version only, without WP System)
- Dimmerabile | Dimmable**
- L - Lunghezza cavo su misura senza WP System p.511**
L - Customized cable lenght without WP System p.511
- S - Lunghezza cavo su misura senza WP System in C.C. p.511**
S - Customized cable lenght without WP System in C.C. p.511

Disponibile su richiesta
Also available

Ganimede S Prodotto | Product



GANIMEDE S


	IP67 kg 0,18 45 mm						
	SUPPLY	W	LM	OPTICS	LED COLOR	CODE	+ FINISHING
	24Vdc	2	170	120°	3000 K	GAN21234	.13
	24Vdc	2	180	120°	4000 K	GAN21244	.13

ALIMENTATORI OBBLIGATORI | POWER SUPPLIES REQUIRED:

24Vdc (2W) IP67

AE24018	[18W]	(1/7 Fixtures)
AE24035	[35W]	(1/14 Fixtures)
AE24060	[60W]	(1/24 Fixtures)

Ganimede L Prodotto | Product



GANIMEDE L

	IP67 kg 0,54 71 mm						
	SUPPLY	W	LM	OPTICS	LED COLOR	CODE	+ FINISHING
	24Vdc	6	660	120°	3000 K	GAN23234	.13
	24Vdc	6	720	120°	4000 K	GAN23244	.13

ALIMENTATORI OBBLIGATORI | POWER SUPPLIES REQUIRED:

24Vdc (6W) IP67


AE24018	[18W]	(1/2 Fixtures)
AE24035	[35W]	(1/4 Fixtures)
AE24060	[60W]	(1/8 Fixtures)

Composizione <i>Composition</i>	-D1	-D2	-D3	-D4	Sistema di controllo <i>Control System</i>
GAN11234.13-Dx <i>Dimmable power supply</i>	Push	-	DALI	1-10V	Alimentatori dimmerabili p.516 <i>Dimmable power supplies</i>
GAN11234.13-Dx <i>Dimmable 24Vdc Controller + 24Vdc power supply</i>	Push	DMX	DALI	1-10V	Centraline 24Vdc dimmerabili p.519 <i>Dimmable 24Vdc Controllers</i>

ACCESSORI NECESSARI ALL'INSTALLAZIONE

NECESSARY ACCESSORIES FOR THE INSTALLATION

Cassaforma | *Housing box* Code: CAQ41



Cassaforma | *Housing box* Code: CAQ62

