



NARVIK

Paletto **IP65**, ideale per l'illuminazione di aree pubbliche e residenziali.

IP65 bollard, ideal for the lighting of public and residential areas.

NARVIK S



NARVIK S




NARVIK M



NARVIK L

NARVIK



Materiale
Material

Corpo e basetta in alluminio anticorrosivo
Anticorrosive aluminium body and base

Basetta in acciaio inox AISI 316L
AISI 316L stainless steel base

Vetro temperato sabbato
Sandblasted tempered glass

Pot. Assorbita
Abs. Power

1 x 6W

Collegamento
Connection

230Vac - Tensione di rete | Mains voltage

Cablaggio
Wiring

Fornito con 50 cm di cavo
Provided with 50 cm cable

Installazione
Installation

A terra con basetta e viti (incluse)
On ground with base and screws (included)

Alimentatore
Power supply

Integrato | Integrated

Finitura
Finishing

- .02 Bianco opaco** | Matt white **RAL9003**
- .05 Grigio opaco** | Matt grey **RAL9006**
- .08 Nero opaco** | Matt black **RAL9005**
- .09 Corten**
- .17 Antracite** | Anthracite




Narvik S Prodotto | Product




Narvik M Prodotto | Product



Narvik L Prodotto | Product



NARVIK S




IP65 **CE** kg 1,16

SUPPLY	W	LM	OPTICS	LED COLOR	CODE	+	FINISHING
230Vac	6	810	-	3000 K	NAR61332	.	.02 .05 .08 .09 .17
230Vac	6	820	-	4000 K	NAR61342	.	.02 .05 .08 .09 .17

Alimentatore integrato | Power supply integrated

NARVIK M




IP65 **CE** kg 1,56

SUPPLY	W	LM	OPTICS	LED COLOR	CODE	+	FINISHING
230Vac	6	810	-	3000 K	NAR62332	.	.02 .05 .08 .09 .17
230Vac	6	820	-	4000 K	NAR62342	.	.02 .05 .08 .09 .17

Alimentatore integrato | Power supply integrated

NARVIK L



IP65 **CE** kg 1,96

SUPPLY	W	LM	OPTICS	LED COLOR	CODE	+	FINISHING
230Vac	6	810	-	3000 K	NAR63332	.	.02 .05 .08 .09 .17
230Vac	6	820	-	4000 K	NAR63342	.	.02 .05 .08 .09 .17

Alimentatore integrato | Power supply integrated

Dimmerazione non disponibile
Dimming not available