



PALLAS

Proiettore **IP67** orientabile, per installazioni a pavimento/parete/soffitto, ideale per l'illuminazione di statue, alberi, portici, ingressi.

*Adjustable **IP67** projector, for floor, wall, and ceiling applications, ideal for the lighting of statues, trees, colonnades, entrances.*



PALLAS 1 - S



PALLAS 1 - S



PALLAS 2 - M



PALLAS 1 - M



PALLAS 2 - M

PALLAS 1

Pallas 1 - S Prodotto | Product

PALLAS 1 - S



Materiale
Material

Corpo in alluminio anticorrosivo verniciato
Varnished anticorrosive aluminium body

Staffa in acciaio inox verniciato
Varnished stainless steel bracket

Vetro trasparente e lente in PMMA
Transparent glass and PMMA lens

Pot. Assorbita
Abs. Power

S version **1 x 2W**
M version **1 x 6W**

Collegamento
Connection

24Vdc - Parallelo | Parallel

Cablaggio
Wiring

Fornito con 50 cm di cavo e WP System
Provided with 50 cm cable and WP System

Installazione
Installation

A terra, a parete o soffitto con staffa (inclusa)
Floor, wall or ceiling mounting with brackets (included)

A terra con picchetto (non incluso)
On ground with peg (not included)

Alimentatore
Power supply

24Vdc (Non incluso | Not included)


Finitura
Finishing

- .02 Bianco opaco | Matt white RAL9003**
- .05 Grigio opaco | Matt grey RAL9006**
- .08 Nero opaco | Matt black RAL9005**
- .09 Corten**
- .18 Verde | Green**

Disponibile su richiesta
Also available

- 5000 K (Solo versione S | S version only)**
- Rosso | Red (Solo versione S | S version only)**
- Verde | Green (Solo versione S | S version only)**
- Blu | Blue (Solo versione S | S version only)**
- RGBW (Solo versione M, senza WP System)**
- RGBW (M version only, without WP System)**

Dimmerabile | Dimmable
Lunghezza cavo su misura senza WP System p.511
Customized cable length without WP System p.511



Pallas 1 - M Prodotto | Product



IP67 CE III WP kg 0,15

	SUPPLY	W	LM	OPTICS	LED COLOR	CODE	+	FINISHING
	24Vdc	2	170	15°	3000 K	PA111231	.	.02 .05 .08 .09 .18
	24Vdc	2	180	15°	4000 K	PA111241	.	.02 .05 .08 .09 .18
	24Vdc	2	170	30°	3000 K	PA111232	.	.02 .05 .08 .09 .18
	24Vdc	2	180	30°	4000 K	PA111242	.	.02 .05 .08 .09 .18
	24Vdc	2	170	60°	3000 K	PA111233	.	.02 .05 .08 .09 .18
	24Vdc	2	180	60°	4000 K	PA111243	.	.02 .05 .08 .09 .18

ALIMENTATORI OBBLIGATORI | REQUIRED POWER SUPPLIES:

24Vdc (2W) IP67

AE24018 [18W] (1/7 Fixtures)
AE24035 [35W] (1/14 Fixtures)
AE24060 [60W] (1/24 Fixtures)

PALLAS 1 - M



IP67 CE III WP kg 0,5

	SUPPLY	W	LM	OPTICS	LED COLOR	CODE	+	FINISHING
	24Vdc	6	660	15°	3000 K	PA112231	.	.02 .05 .08 .09 .18
	24Vdc	6	720	15°	4000 K	PA112241	.	.02 .05 .08 .09 .18
	24Vdc	6	660	30°	3000 K	PA112232	.	.02 .05 .08 .09 .18
	24Vdc	6	720	30°	4000 K	PA112242	.	.02 .05 .08 .09 .18
	24Vdc	6	660	60°	3000 K	PA112233	.	.02 .05 .08 .09 .18
	24Vdc	6	720	60°	4000 K	PA112243	.	.02 .05 .08 .09 .18

ALIMENTATORI OBBLIGATORI | REQUIRED POWER SUPPLIES:


24Vdc (6W) IP67

AE24018 [18W] (1/2 Fixtures)
AE24035 [35W] (1/4 Fixtures)
AE24060 [60W] (1/8 Fixtures)

Composizione Composition	-D1	-D2	-D3	-D4	Sistema di controllo Control System
PA111231.02-Dx Dimmable power supply	Push	-	DALI	1-10V	Alimentatori dimmerabili p.516 Dimmable power supplies
PA111231.02-Dx Dimmable 24Vdc controller + 24Vdc power supply	Push	DMX	DALI	1-10V	Centraline 24Vdc dimmerabili p.519 Dimmable 24Vdc Controllers

ACCESSORI | ACCESSORIES

Picchetto | Peg Code: PI002



PALLAS 2

NEW



Materiale
Material

Corpo in alluminio anticorrosivo verniciato
Varnished anticorrosive aluminium body

Staffa in acciaio inox verniciato
Varnished stainless steel bracket

Vetro trasparente e lente in PMMA
Transparent glass and PMMA lens

Pot. Assorbita
Abs. Power

S version **2 x 2W**
M version **2 x 6W**

Collegamento
Connection

24Vdc - Parallelo | Parallel

Cablaggio
Wiring

Fornito con 50 cm di cavo e WP System
Provided with 50 cm cable and WP System

Installazione
Installation

A terra, a parete o soffitto con staffa (inclusa)
Floor, wall or ceiling mounting with brackets (included)

A terra con picchetto (non incluso)
On ground with peg (not included)

Alimentatore
Power supply

24Vdc (Non incluso | Not included)


Finitura
Finishing

- .02 Bianco opaco** | Matt white RAL9003
- .05 Grigio opaco** | Matt grey RAL9006
- .08 Nero opaco** | Matt black RAL9005
- .09 Corten**
- .18 Verde** | Green


Disponibile su richiesta
Also available

- 5000 K** (Solo versione S | S version only)
- Rosso** | Red (Solo versione S | S version only)
- Verde** | Green (Solo versione S | S version only)
- Blu** | Blue (Solo versione S | S version only)
- RGBW** (Solo versione M, senza WP System)
- RGBW** (M version only, without WP System)
- Dimmerabile** | Dimmable
- Lunghezza cavo su misura senza WP System p.511**
Customized cable length without WP System p.511

Pallas 2 - S Prodotto | Product



Pallas 2 - M Prodotto | Product



PALLAS 2 - S



IP67 CE III WP kg 0,32

	SUPPLY	W	LM	OPTICS	LED COLOR	CODE	+	FINISHING
	24Vdc	4	340	15°	3000 K	PA211231	.02 .05 .08 .09 .18	
	24Vdc	4	360	15°	4000 K	PA211241	.02 .05 .08 .09 .18	
	24Vdc	4	340	30°	3000 K	PA211232	.02 .05 .08 .09 .18	
	24Vdc	4	360	30°	4000 K	PA211242	.02 .05 .08 .09 .18	
	24Vdc	4	340	60°	3000 K	PA211233	.02 .05 .08 .09 .18	
	24Vdc	4	360	60°	4000 K	PA211243	.02 .05 .08 .09 .18	

ALIMENTATORI OBBLIGATORI | REQUIRED POWER SUPPLIES:

24Vdc (4W) IP67

- AE24018 [18W] (1/3 Fixtures)
- AE24035 [35W] (1/7 Fixtures)
- AE24060 [60W] (1/12 Fixtures)

PALLAS 2 - M



IP67 CE III WP kg 1,01

	SUPPLY	W	LM	OPTICS	LED COLOR	CODE	+	FINISHING
	24Vdc	12	1320	15°	3000 K	PA212231	.02 .05 .08 .09 .18	
	24Vdc	12	1440	15°	4000 K	PA212241	.02 .05 .08 .09 .18	
	24Vdc	12	1320	30°	3000 K	PA212232	.02 .05 .08 .09 .18	
	24Vdc	12	1440	30°	4000 K	PA212242	.02 .05 .08 .09 .18	
	24Vdc	12	1320	60°	3000 K	PA212233	.02 .05 .08 .09 .18	
	24Vdc	12	1440	60°	4000 K	PA212243	.02 .05 .08 .09 .18	

ALIMENTATORI OBBLIGATORI | REQUIRED POWER SUPPLIES:

24Vdc (12W) IP67

- AE24018 [18W] (1 Fixture)
- AE24035 [35W] (1/2 Fixtures)
- AE24060 [60W] (1/4 Fixtures)

Composizione Composition	-D1	-D2	-D3	-D4	Sistema di controllo Control System
PA211231.02-Dx Dimmable power supply	Push	-	DALI	1-10V	Alimentatori dimmerabili p.516 Dimmable power supplies
PA211231.02-Dx Dimmable 24Vdc controller + 24Vdc power supply	Push	DMX	DALI	1-10V	Centraline 24Vdc dimmerabili p.519 Dimmable 24Vdc Controllers

ACCESSORI | ACCESSORIES

Picchetto | Peg Code: PI002

