





## VITESSE PLUS

Un profilo lineare che si poggia con leggerezza sulla parete per valorizzare i volumi della stanza. Vitesse Plus è un apparecchio da parete bidiffusione, completo di moduli a LED ad alta efficienza. Realizzato in alluminio estruso verniciato a polvere epossipoliestere e fornito di diffusore in policarbonato opalino, l'apparecchio è predisposto per la mono accensione. Driver e accessori in acciaio zincato per l'installazione a parete inclusi. Doppia accensione e versione dimmerabile disponibili su richiesta. Il grado di protezione contro la penetrazione di polvere, corpi solidi e liquidi è IP40.

*A linear profile which lightly caresses the wall and emphasizes the volumes of the room with its light. Vitesse Plus is a single switch double emission wall luminaire complete with high efficiency LED modules. It is made from epoxy powder coated finish aluminum stabilized with UV rays and provided with protective screens made from polycarbonate. Driver and fixing accessories in galvanized steel included. Double switch and dimmable version available on request. The degree of protection against the penetration of dust, solid objects and liquids is IP40.*

## VITESSE PLUS H127 BIEMISSIONE

codice	W	Lm (3000K)	lifetime	
<b>9645.2...</b>	2x6	2x820	60.000h	L80/B20
<b>9646.2...</b>	2x12	2x1635	60.000h	L80/B20
<b>9647.2...*/**</b>	2x18	2x2450	60.000h	L80/B20
<b>9648.2...*/**</b>	2x24	2x3270	60.000h	L80/B20
<b>9649.2...*/**</b>	2x30	2x4085	60.000h	L80/B20



mono accensione / *single switch* \*doppia accensione a richiesta / *double switch on request*

/DIMM2 dimmerabile protocollo DALI 9645.2 escluso / *9645.2 excluded*

/DIMM3 dimmerabile switch-DIM 9645.2 escluso / *9645.2 excluded*

\*\*/EM emergenza

SL	LED
AL	incluso / <i>included</i>
	130°
TC	.30 per 3000K / .40 per 4000K
IP	40
CRI	>80
SDCM	3
EEL	A++
RG	0
02	Nero opaco / <i>Matt black</i>
09	Bianco opaco / <i>Matt white</i>







