Sys

The new elegant and modular track system that allows the various light modules to be fast and easily installed and repositioned by simple clipping and sliding, with a reliable mechanical coupling.

Anyone

Easy and fast plug in and plug out low voltage Sys modules.

Anytime

Sys lets the desired selection of different light modules to be easily adapted on site and over time.

Anyway

Customisable Laser-thin, minimalist: design the layout, define the size.

Anywhere

Sys couples general and accent lighting for staging key spaces or objects.

Anykind

Choose from a range of modules featuring the latest advances in light definition.

Portugal

Porto Head Office / Factory
R. Mauricio Lourenço Oliveira 196,
4405-034 Vila Nova de Gaia
+351 223 710 419

Lisbon Office
Edifício Mar do Oriente
Rua do Pólo Norte 16, 0.1
1990-266 Lisboa
+351 211 919 300

Brazil

São Paulo Head Office
Av. 9 de Julho 4939, 126 A
CEP 01407-200 Jardim Paulista
São Paulo – SP
+55 11 3045 3095

São Paulo Factory
Rodovia Vice Prefeito Hermenegildo
Tonoli 1500, Módulo 12
CEP 13213-089 Distrito Industrial.
Jundiaí – SP

Rio de Janeiro Office
+55 21 972 866 844

Spain

Barcelona Office
+34 646 193 109
span@om-light.com

mail@om-light.com
www.om-light.com
_omlight

Uw

The asymmetrical reflector drapes vertical surfaces with a controlled, comfortable and uniform sheet of light.

inVision

With the efficient and compact double focal lens, inVision creates great light distribution from an invisible source.

Diffuse

Frosted polycarbonate diffuser for all applications where diffused light is required.

InFinit

The glare control and visual comfort of the Lightstream optic make inFinit ideal for workplaces. A continuous line of light subtly integrated in architecture.

Onit

An adjustable spotlight that expands creative possibilities in lighting design, Onit is the ideal, playful solution for light modelling.

Over

Featuring the high-definition Lightcore optic, Over is the spotlight with a deep-set light source offering maximum cut-off angles.

Blind

A non-luminous cover plate with tailored length to create pauses and spacing between light modules.

O/M

COMPETE 2020 · PORTUGAL 2020 · UNIÃO EUROPEIA Fundo Europeu de Desenvolvimento Regional

Sys

With a variety of solutions
to perform the right lighting
functions for different tasks,
choose from a range of modules
featuring the latest advances
in light definition.

Onit

Uw

InFinit

InVision

Flexibility / Bespoke

Customisable
aluminium profile
enclosing a continuous
48 Vdc track, Sys
allows amazingly subtle
and flexible lighting
integration. Sys lets
the desired selection of
different light modules
to be easily adapted on
site and over time.

Overview

Structure

1 Profile
2 End caps
3 Fitting accessories
4 Profile connections

Modules

A inFinit
B Uw
C inVision
D Diffuse
E Onit/Over
F Indirect
G Blind

Structure

Enabling different
installations, Recessed,
Surface or Pendant
direct/indirect profiles
allow the various light
modules to be fast
and easily installed,
and repositioned by
simple clipping and
sliding, with a reliable
mechanical coupling.

Body
Extruded aluminium profile with
a 48 Vdc track in texture-finish
paint: white or black. Aluminium
end caps in texture-finish paint.

Power Supply
48 Vdc

Accessories
Fitting accessories for different
applications are available.

Profile

Recessed

Surface

Pendant

Pendant direct/indirect

Modules

inFinit
LED CRI > 90 3000K, 4000K; CRI > 80 Tunable White
> 50.000h, L80/B10 | 2-step MacAdam | IP20 | 48Vdc
Flood / White Flood | 300to 1200mm

Uw
LED CRI > 90 2700K, 3000K; CRI > 80 4000K, Tunable White
> 50.000h, L80/B10 | 2-step MacAdam | IP20 | 48 Vdc
Asymmetric | 300 to 1200 mm

inVision
LED CRI > 90 2700K, 3000K; CRI > 80 4000K, Tunable White
> 50.000 h, L80/B10 | 2-step MacAdam | IP20 | 48 Vdc
Medium / Flood | 300 to 1200 mm

Diffuse
LED CRI > 80 2700K, 3000K, 4000 K
> 50.000h, L80/B10 | 3-step MacAdam | IP20 | 48 Vdc
Diffuse | 600 to 1200 mm

Indirect
LED CRI > 90 2700K, 3000K, 4000K; CRI > 80 Tunable White
> 50.000h, L80/B10 | 2-step MacAdam | IP20 | 48 Vdc
Batwing | 600 and 1200 mm

Onit
Over
LED CRI > 90 2700K, 3000K; CRI > 80 4000K
> 50.000h, L80/B10 | 2-step MacAdam | IP20 | 48 Vdc
Spot / Medium / Flood | Ø45 mm (Over)
Spot / Medium | Ø45 mm (Onit)

Blind
Customisable

Sys

om-light.com

O/M